



999.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- Intel® Q67 Express Chipset
- Supports Intel LGA 1155 Socket Core™ i3, i5, i7 & Pentium Processors
- 2 * Dual Channel DDR3-1333/1066 up to 16GB
- Intel 82579LM & 82574L Gigabit LAN
- Intel Active Management Technology (iAMT 7.0)
- PCI Express x16 Slot
- Integrated 24-bit Dual Channel LVDS
- 4-port SATAII 3Gb/s & 2-port SATA III 6Gb/s with RAID 0, 1, 5, 10 & JBOD Support
- HDMI, and VGA Video Outputs
- Built-in Watchdog Timer Technology
- Mini-ITX Form Factor (170mm x 170mm)

• **CPU**
• **Chipset**

• **Memory**

• **Expansion Slots**

• **Storage**

INTEL® LGA 1155 Socket Core i7/i5/i3/Pentium Processor
INTEL® Q67 Chipset
Clock 100MHz
2 * 240 pin 4GB 1333/1066 Dual CH DDR3 SDRAM DIMM Max. up to 16GB
1 *PCIe x 16
2 * Serial ATA3 6Gb/s & 4 * Serial ATA2 3Gb/s connectors support RAID 0, 1, 5, 10

- **Audio** VIA VT1705 6-Channel HD Audio CODEC
- **Ethernet LAN** Intel 82579LM & 82574L PCI-E Gigabit Ethernet LAN
- **LVDS** Onboard 24-bit dual channel LVDS connector
- **USB** Embedded 10 * USB 2.0/1.1
- **Special Features** Support ACPI S3
Support CPU Smart FAN
Support Watch Dog

- **Rear Panel I / O** 6 * USB 2.0/1.1 ports
1 * PS2/KB Connector
2 * RJ-45 port
1 * HDMI port
1 * COM port
1 * VGA port
3 * Audio Phone Jack

- **Internal I / O** 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports
CPU /NB / Chassis Fan connectors
1 * GPIO header
1 * COM header(RS232/422/485)
1 * IR header
1 * Chassis Intrusion header
1 * AUDIO header
1 * 24-pin & 4-pin 12V ATX Power connector

- **BIOS** AMI EFI 64MB SMT Flash ROM
- **Form Factor** Mini-ITX Form Factor (170mm x 170mm)
- **Functional** ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation

- **Certificate** CE, FCC, RoHS
- **Temperature** Operating within 0~60 centigrade
Storage within -20-85 centigrade

Product Accessories

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield