



749.00 EUR
incl. 19% VAT, plus [shipping](#)



Support: [Specifications](#)

- Single Intel® Atom Denverton processor C3000 Series SoC
- 2x DIMM slots support up to 32GB/64GB UDIMM/RDIMM ECC DDR4 2400/2133, or 1x DIMM slot support up to 16GB/ 32GB UDIMM/ RDIMM ECC DDR4 1866
- 1x PCI-E Gen3 x8 slot (w/ x8 link or x2 link)*Low-profile supported only
- 1x SFI connector or w/M3227L8-X557-2C (-2T-C958 SKU only)
- 1x M.2 connector (2242/2260), 2x SATA HDDs by SATA-III connectors running at 6.0Gb/s (RAID Non-support)
- 2x GbE (via Realtek RTL8111H) or 2x 10GbE (from M3227L8-X557-2C TYAN Mezz Card) + 2x GbE (via Realtek RTL8111H) (-2T-C958 SKU)
- Mini-ITX 6.69" x 6.69" (170 x 170mm)

TYAN S3227 (S32272NR-C858) Specifications

Processor	Supported CPU Series	(1) Intel Atom Denverton processor C3858 SoC
	Thermal Design Power (TDP) wattage	25W
Chipset	Super I/O	NCT6683D-T

Memory	Supported DIMM Qty	(2) DIMM slots
	DIMM Type / Speed	UDIMM/RDIMM ECC DDR4 2400
	Capacity	Up to 32GB/64GB
Expansion Slots	Memory voltage	UDIMM/RDIMM
	PCI-E	1.2V
	Others:	(1) PCI-E Gen3 x8 slot / *Low-profile supported only
LAN	Port Q'ty	(1) SFI connector
	Controller	(2) GbE ports
Storage	Connector	Realtek RTL8111H
	Controller	(2) SATA
	SATA	Intel Atom Denverton processor
	Speed	C3858 SoC CPU
	RAID	6.0 Gb/s
Input /Output	M.2 connector	Non-support
	USB	(1) M.2 connector (2242/2260) by PCI-E interface
	COM	(2) USB3.0 ports (via cable) / (2) USB3.0 ports (at rear)
	RJ-45	(1) header
	Front Panel	(2) GbE ports
	SATA	(1) 2 x 5 header
	Power	(2) SATA-III connectors
System Monitoring	Chipset	SSI/ATX 24-pin + 4-pin power connectors
	Fan	NCT6683D-T
	Temperature	Total (3) 4-pin headers Monitors temperature for CPU & system environment / Monitors temperature for CPU & memory & system environment
	Voltage	Monitors voltage for CPU, memory, chipset & power supply
	LED	Fan fail LED indicator / Over temperature warning indicator
	Others	Watchdog timer support
	Brand / ROM size	AMI / 16MB
BIOS	Feature	ACPI 3.0/ACPI sleeping states S4,S5 / SMBIOS 2.8/PnP/Wake on LAN / Boot from USB device/PXE via LAN/Storage / User Configurable FAN PWM Duty Cycle / Console Redirection
	Physical Dimension	mini-ITX
Regulation	Board Dimension	6.69" x 6.69" (170 x 170mm)
	FCC (DoC)	Class B
Operating Environment	CE (DoC)	Class A
	Operating Temp.	10° C ~ 35° C (50° F~ 95° F)
	Non-operating Temp.	- 40° C ~ 70° C (-40° F ~ 158° F)
RoHS	In/Non-operating Humidity	90%, non-condensing at 35° C
	RoHS 6/6 Compliant	Yes
Operating System	OS supported list	Please refer to our AVL support lists.

Package Contains

Motherboard	(1) S3227 Motherboard
Manual	(1) Quick Installation Guide
Installation CD	(1) TYAN installation CD