



- | | |
|-------------------|---|
| Product Dimension | – 264 (W) * 199.4 (D) * 38 (H) mm |
| MB Model | – JNF595-H110 / Mini-ITX |
| Part No | – HBJC511F595-H110-B (non-WIFI) / HBJC511F595W-H110-B (WIFI) |
| BIOS | – AMI 64MB SMT Flash ROM |
| CPU/Chipset | – INTEL® LGA 1151 Socket Core i7/i5/i3/Pentium Processor (35W)
– INTEL® H110 express chipset
Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload. |
| Memory | – 2 * 204-pin SO-DIMM slots supporting dual channel DDR4-21330 up to 32GB |
| Storage | – 1 * 2.5" SATA3 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm)
– 1 * Full-size mSATA/mini-PCI Express shared slot |
| Network | – 1 * Intel i219V Gigabit LAN
– 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model) |
| Rear Panel I/O | – 4 * USB 3.0 ports
– 1 * HDMI 1.4A(Max. Resolution: 1920*1080@60Hz)
– 1 * DP1.2(Max. Resolution: 4096*2304@60Hz)
– 1 * RJ45
– 1 * Line-out, 1 * Mic-in
– 2 * COM (RS232)
– 2 * Antenna holes(WiFi only)
– 1 *DC-In Jack |
| Front Panel I/O | – 1 * Power button , 1 * Reset button
– 1 * Power LED , 1 * HDD LED
– 2 * USB 2.0 ports
– 1 * Line-out, 1 * Mic-in |
| Power Source | – FSP AC-DC Adapter_DC19V_6.3A_120W
– AC 90~240V input |
| Compliance | – CE, FCC, RoHS, ErP Readyk |
| Temperature | – Operating Temperature: 0~50°C
– Storage Temperature: -10~70°C |

Packing	– Net Weight■2.4KG – Gross Weight■3.4KG – Color Box Dimension■ 406 (W) * 148 (D) * 380 (H) mm
OS Support	– Skylake CPU support Win7, Win8, Win10. – Kabylake CPU only support Win10.
Warranty	– 2 Year limited warranty