

469.00 EUR
incl. 19% VAT, plus shipping

- Intel J6412 !
- 2 x 2.5GbE !
- 4 x COM !
- Fanless !

- Fanless embedded Box PC with Intel® Celeron® Processor J Series (formerly Elkhart Lake)
- Intel® J6412 with TDP 10W
- Memory: 1 x DDR4 3200/2933MHz, up to 32GB
- High-Speed Networking: 2 x Intel® I225-V 2.5GbE
- Storage: M.2 M-Key with SATA interface and internal 2.5-inch SATA drive bay
- 4K Display: HDMI® 2.0b with up to 4096 x 2160@60Hz

SYSTEM	
CPU	Intel® Celeron® Processor J Series (formerly Elkhart Lake)
CHIPSET	Intel® J6412 (TDP 10W)
SYSTEM MEMORY	1 x DDR4 3200/2933MHz up to 32GB
STORAGE DEVICE	1 x M.2 M key (2242/2280, SATA Interface) 1 x 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ?10mm)
POWER	
POWER REQUIREMENT	MB : DC-in 12V Adapter : AC100~240V / DC12V_5A_60W
DISPLAY	
DISPLAY INTERFACE	1 x HDMI2.0b (Max Resolution : 4096x2160@60Hz)
LAN	
ETHERNET	2 x Intel® I225-V, 2.5GbE
SYSTEM I/O	
REAR I/O	1 x DC Jack (12V DC-in) 4 x COM (4 x RS232 or 2 x RS232 + 2 x RS485) 1 x HDMI2.0b 2 x USB3.2 Gen.1 4 x USB2.0 2 x RJ45 1 x Line-out 1 x MIC 1 x Power Button
EXPANSION	
M.2	1 x M.2 E key Socket for WIFI/BT (2230, PCI-Ex1+USB2.0 Interface)
MECHANICAL	

MOUNTING	Desktop, Wallmount
DIMENSIONS (W x D x H)	200.0(W) x 180.4 (D) x 59.5 (H) mm
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-10°C ~ 50°C (14°F ~122°F) (Under the condition of using M.2 interface SSD)
STORAGE TEMPERATURE	-20°C ~ 60°C (-4°F ~140°F)
OPERATING HUMIDITY	10 ~ 90% @ 40°C, non-condensing
CERTIFICATION	CE/FCC Class A , LVD